1. Dimensions:



2. Schematic:



3. Electrical Specifications

Rated Voltge: 80Vdc

Rated Current: 0.5Aac

DC Res.: 0.25 Ohms Typ, 0.30 Ohms Max each wdg.

OCL: 470uH Min @100KHz, 0.1V Each Wdg.

LL: Pin4–1 0.20uH Typ @100KHz, 0.1V Tie 3–2

Isolation: 200Vrms

Notes:

1. Solderability: Leads shall meet MIL–STD–202G, Method 208H for solderability.
2. Flammability: UL94V–0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from –40°C to +85°C
6. Storage Temperature Range: –55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. AEC–Q200 Certified Product

DOC. REV: A/3

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS ® www.XFMRS.com	Title: Common Mode Choke		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ±0.010 Dimensions in Inch	P/N: XF4706–00SM		REV A
	DWN.	李小锋	Jul–21–20
	CHK.	廖玉坤	Jul–21–20
Scale 2.5:1 SHT 1 OF 1	APP.	TCH	Jul–21–20

XF0409-00SM

P/N:95-Q922-01

TAPE AND REEL SPECIFICATION:

NOTES:

1) PROCESS IN ACCORDANCE WITH EIA-481-2 STANDARDS
   * TAPE LEADER DIMENSION 15.30" MIN.
   * TAPE TRAILER DIMENSION 6.30" MIN.
2) PARTS SHOULD BE PACKAGED IN ACCORDANCE WITH ESD GUIDELINES IN EIA-541.
3) REEL LABEL: 'A' * PART NUMBER
   * QUANTITY
   * DATE CODE
   'B'- ANTI-STATIC CAUTION LABEL
4) 800PCS PER 13"REEL



REEL AND TAPE ORIENTATION

DETAIL A



13" REEL DIAMETER

FOR PARTS:XF0409-00SM
XF0474-00SM
XF0516-00SM

DOC. REV.A/1

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc	Title: 4 Pins T&R SPEC		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxs ±xxxxx Dimensions in mm	P/N:XFxxxx-00SM		REV: A
	DWN.	KONG	MAR-21-06
	CHK.	YK Liao	MAR-21-06
SHT 2 OF 2	APP.	BW	MAR-21-06