1. Mechanical Dimensions:



Top view



Side view



Front View



Typical Pad Layout



Bottom view

2. Schematic:



3. Electrical Specifications: @25°C

OCL: 15uH±20% @100KHz, 0.1V

Q: 12 Min @100KHz, 0.1V

DCR: 45.6 mOhms Max

Isat: 8.00A (Based on 20% Typ drop in OCL)

Irms: 4.50A (Based on 40°C Typ Temp Rise)

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component

DOC. REV: A/4

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc www.XFMRS.com	Title: XFHCL11MB SERIES INDUCTORS		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFHCL11MB-150M		REV. A
	DWN.	Yuan	Apr-04-14
	CHK.	YK Liao	Apr-04-14
SHEET 1 OF 1	APP.	DDC	Apr-04-14