1. Mechanical Dimensions:



Top view



Side view



Front View



Typical Pad Layout



Bottom view

2. Schematic:



3. Electrical Specifications: @25°C

OCL: 0.56uH±20% @100KHz 0.1V

Q: tbd Min @100KHz 0.1V

Isat: 30Adc (Based on 30% drop in OCL)

DCR: 2.5 mOhms Max

Hipot: 250Vac 6 second, Coil to Core, 1mA Max

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -30°C to +100°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component

DOC. REV: A/1

XFMRS Inc www.XFMRS.com	Title: SMD POWER INDUCTORS		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFHCL11MB-R56M		REV. A
	DWN.	Feng	Jun-28-11
	CHK.	YK Liao	Jun-28-11
SHEET 1 OF 1	APP.	BW	Jun-28-11

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.