1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications: @25°C

OCL: 3.3uH±20% @100KHz 0.1V

Q: tbd Min @100KHz 0.1V

Isat: 3.0Adc (OCL 20% Typ drop in OCL)

Irms: 2.3Adc (OCL 40°C Temp Rise)

DCR: 145 mOhms Max, 128 mOhms Typ

SRF: tbdMHz Typ

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +105°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 250C Max
12. Outsourced item processed & controlled under XFMRS QA system

DOC. REV: A/1

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc www.XFMRS.com	Title: INDUCTOR		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFHCL19-3R3M		REV. A
	DWN.	Yuan	Jan-19-17
	CHK.	YK Liao	Jan-19-17
SHEET 1 OF 1	APP.	BW	Jan-19-17