1. Mechanical Dimensions:



(TOP VIEW)





(BOTTOM VIEW)



(Land Patterns)

2. Schematic:



3. Electrical Specifications: @25°C

OCL: 0.56uH±20% @100KHz, 1V

Q: tbd Min @100KHz, 1V

DCR: 10 mOhms Max, 8.0 mOhms Typ

Isat: 15Adc (Based on 20% drop in OCL)

Irms: 10.0Adc (Based on 40°C Temp Rise)

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. All listed parameters are to be within tolerance from -40°C to +105°C unless otherwise noted.
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 250°C Max.
12. Outsourced item processed & controlled under XFMRS QA system

PRELIMINARY

DOC. REV: A/-

XFMRS Inc www.XFMRS.com	Title: SMT POWER INDUCTOR		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFHCL22MB-R56M		REV. A
	DWN.	Yuan	Nov-12-14
	CHK.	YK Liao	Nov-12-14
SHEET 1 OF 1	APP.	BSJ	Nov-12-14

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.