






1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications: @25°C

OCL: 0.68uH±25% @100KHz 10mA

Q: 8 Min @100KHz 10mA

DCR: 0.72 mOhms±10%

Irms: 26.0A (Based on 40°C Temp Rise)

Isat: 38.0Adc (Based on 30% Typ drop in OCL)

SRF: 108MHz Min

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +125°C
6. Storage Temperature Range: -40°C to +60°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 245C Max.
12. DCR is measured at solder joint, not on terminal

DOC. REV: A/4

XFMRs Inc www.XFMRs.com	Title: INDUCTOR		
	UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25 Dimensions in MM	P/N: XFSMC2-R68M	REV. A
SHEET 1 OF 1	DWN.	Yuan	Jul-15-13
	CHK.	YK Liao	Jul-15-13
	APP.	DDC	Jul-16-13