1. Mechanical Dimensions:



(Top View)





Suggested Pad Layout

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component

2. Schematic:



3. Electrical Specification:

Common Mode Impedance: 3000 Ohms Typ @100MHz
Rated Current: 500mA
Rated Voltage: 50Vdc
Insulation Resistance: 10 MOhms min
Withstand Voltage: 125Vdc
DC Resistance: 0.3 Ohms Max, Each Wdg



DOC REV: A/12

PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.

XFMRS Inc www.XFMRS.com	Title: EMI filter		
UNLESS OTHERWISE SPECIFIED TOLERANCES: .xx ±0.25. Dimensions in MM	P/N: XFWCMC636347-302		Rev. A
	DWN.	Mei Chen	Aug-05-10
	CHK.	YK Liao	Aug-05-10
SHEET 1 OF 1	APP.	BW	Aug-05-10